




Premium White Washdown Hose

Features:

- PPI's Premium Cold Water Washdown Hose is flexible, weather resistant and durable.
- Ideal for washdown in dairies and for watering large parks or gardens.
- UV stabilised for outdoor use.
- Exhibits excellent flexibility at low temperatures.
- Very durable with excellent ply adhesion.
- 25 mm Premium Washdown Hose is the recommended size and quality for the Nelson 8401E Rain Train (max length 60m)
- The recommended minimum bend radius is five times the outside diameter. This needs to be considered when designing hose reels or hangers.
- Serrated profile provides a positive grip.



Specifications:

Nominal Internal Diameter		Min. Wall Thickness	Working Pressure		Min. Burst Pressure	
12.5	1/2"	3.2	1400	200	5600	800
19	3/4"	3.9	1400	200	5600	800
25	1"	4.2	1400	200	5600	800
32	1 1/4"	5.0	1100	160	4400	640
38	1 1/2"	5.5	1000	150	4000	600

Coil Dimensions:

Nominal Internal Diameter (mm)	Weight (kg)	Coil Dimensions			
		Length (m)	Width (mm)	ID	OD (mm)
12.5	4	20	95	260	400
		100	150	260	590
19	7.8	20	150	400	450
		100	200	260	760
32	15.2	20	210	400	635
		100	270	610	1180
38	18.46	20	240	400	660
		100	300	600	950

AUSTRALIA – PPI CORPORATION PTY LTD (ABN 79 010 656 005)
QLD Sales Office Ph: (07) 3865 2300 Fax: (07) 3857 0058
Townsville Sales Office Ph: (07) 4779 7322 Fax: (07) 4779 2509
NSW Sales Office Ph: (02) 9820 5955 Fax: (02) 9820 5082
VIC Sales Office Ph: (03) 9791 3700 Fax: (03) 9791 3900
SA Sales Office Ph: (08) 8447 2611 Fax: (08) 8447 8117
TAS Sales Office Ph: (03) 6248 5933 Fax: (03) 6248 5988
WA Sales Office Ph: (08) 9244 5433 Fax: (08) 9244 5499
NT Agent Territory Hardware Ph: (08) 8947 1250 Fax: (08) 8984 4461

EXPORT ENQUIRIES Ph: +61 7 3865 3699 Fax: +61 7 3857 0058

NEW ZEALAND—PPI CORPORATION (NZ) LIMITED
 Christchurch Ph: (03) 313 7956 Fax: (03) 313 5551

EMAIL: sales@ppi.com.au
HOME PAGE: www.ppi.com.au

Date: 16 December 2004
Code: ZM/LT6PHWASH