



CONTROLLER Accessories

For 2001, Nelson introduced the EZ Pro™ series of irrigation controllers and the EZ Command™ Radio control unit. Ideal for residential and commercial applications, these units offer superior electronics and flexible programming. Now Nelson offers a variety of accessories for the EZ Pro controller and EZ Command Radio unit making them even more flexible. Nelson's Rain-Trip™ Rain Sensor for unneeded watering, a pedestal for out of the way mounting needs, the Radio module giving your EZ Pro radio capabilities with the EZ Command, and a Protective Jacket for the EZ Command for when you're out on the job site.

8000
Pump start relay

8501
Rain-Trip™ Rain Sensor

8602
EZ Command™ Radio Module

8607
EZ Command™ Protective Jacket

8609
EZ Pro™ Controller pedestal

CONTROLLER Accessories

8602 radio module



EZ Command™ Radio Module

- Upgrades base model EZ Pro by adding radio capability
- Easy to install - just plug it in!

8607 protective jacket



EZ Command™ Protective Jacket

- Helps protect EZ Command™ against normal daily use
- Clip located on jacket for belt configuration

8609 pedestal



EZ Pro™ Controller pedestal

- The Model 8609 EZ Pro Pedestal is designed to be used with all EZ Pro controllers. It is designed to maximize radio performance on EZ Pro radio equipped models.
- Entire front panel removable for easy access to wiring
- Made of industrial grade non-rusting stainless steel
- 35" H x 10.5" W
- Weight: 30 lbs
- Controller mounting hardware and instructions included.

8501 rain sensor



Rain-Trip™ Rain Sensor

- Unit ready for bracket mount or 1/2" conduit/pipe thread mount at bottom
- Adjusts easily from 1/8" to 1" rainfall
- Compatible with most controller brands (Ready for normally-closed or normally-open hookup)
- Supplied with 25 feet of hookup wire
- Saves unneeded watering
- Designed to be used with low voltage irrigation systems only

8000 pump start relay



Pump start relay

Box Features

- Waterproof, dust proof, outdoor mount, foam seal
- Knockouts provided on all sides, 1/2" and 3/4"
- Sealing plugs provided to waterproof mounting screws

Relay Features

- Contactor UL, CSA approvals
 - No exposed parts. Contacts and coil fully enclosed
 - Finger-proof construction. No additional cover needed
 - Pressure wire screw terminal accepts 24 to 10 AWG wire
 - Single and 3 phase. One relay will fit many applications
- 1 Phase - 1HP 120 volt
2HP 200-240 volt
3 Phase - 3HP 200-240 volt
3HP 440-480 volt