

Features:

- Neta's Premium Cold Water Washdown Hose is flexible, weather resistant and durable.
- Ideal for washdown in dairies and for watering large parks or gardens.
- UV stabilised for outdoor use.
- Exhibits excellent flexibility at low temperatures.
- Very durable with excellent ply adhesion.
- The recommended minimum bend radius is five times the outside diameter. This needs to be considered when designing hose reels or hangers.
- Serrated profile provides a positive grip.



Specifications:

Nominal Internal Diameter		Min. Wall Thickness	Working Pressure		Min. Burst Pressure	
19	¾"	3.9	1400	200	5600	800
25	1"	4.2	1400	200	5600	800
32	1¼"	5.0	1100	160	4400	640
38	1½"	5.5	1000	150	4000	600

Coil Dimensions:

Nominal Internal Diameter (mm)	Weight (kg)	Coil Dimensions			
		Length (m)	Width (mm)	ID (mm)	OD (mm)
19	11.8	30	130	270	450
	39.2	100	200	400	730
25	16.1	30	150	270	500
	53.6	100	230	400	870
32	16.0	30	200	400	640
	24.1	60	340	610	1170
38	31.0	30	240	400	660
	62.0	60	300	600	950

AUSTRALIA – PPI Corporation Pty Ltd (ABN 79 010 656 005)

QLD Sales Office Ph: (07) 3865 2300 Fax: (07) 3857 0058
Townsville Sales Office Ph: (07) 4779 7322 Fax: (07) 4779 2509
NSW Sales Office Ph: (02) 8706 2400 Fax: (02) 8706 2499
VIC Sales Office Ph: (03) 9791 3700 Fax: (03) 9791 3900
SA Sales Office Ph: (08) 8447 2611 Fax: (08) 8447 8117
TAS Sales Office Ph: (03) 6248 5933 Fax: (03) 6248 5988
WA Sales Office Ph: (08) 9212 3200 Fax: (08) 9355 0675
NT Agent Territory Hardware Ph: (08) 8947 1250 Fax: (08) 8984 4461

EXPORT ENQUIRIES Ph: +61 7 3865 3699 Fax: +61 7 3857 0058

NEW ZEALAND – PPI Corporation Pty Ltd
 Christchurch Ph: (03) 313 7956 Fax: (03) 313 5551

EMAIL: sales@ppi.com.au
 WEB: www.homeirrigation.com.au

Date: 12th September 2007
 Code: ZM/LT6PHWASH